

'EA' Series - Floor Systems

Features

EA Series

INT.

Application

Seismic lovement

FLOOR

- System designed to be installed in recessed floor
- Seismic Pan System for accommodating various floor finishes
- Negligible sight line makes system popular
- Steel central flanges allows swift shift between positive and negative movements
- Vapor and Fire Barriers are optionally available

Straight Application EAS


Corner Application EAC


21

provides swift correction after seismic movement and silent passage to pedestrians and wheels System allows full seismic movements

Specially designed spring assembly under pan

- System allows excellent shear movement
- Load rated subject to joint opening
- ADA compliant
- Also available in Stainless Steel and Brass





	Application	Code	JO	SH	SW	± Movement (%)			Load
	Application		Millimeter			Horizontal	Vertical	Shear	(Ton)
	Straight (S)	EAS 02	51	50	206	100	12.5	Excellent	3
		EAS 03	76	50	231	100	12.5	Excellent	2
		EAS 04	102	50	257	100	12.5	Excellent	1
		EAS 06	152	50	308	100	12.5	Excellent	1
		EAS 08	203	50	359	100	12.5	Excellent	1
		EAS 10	254	62	435	100	12.5	Excellent	1
		EAS 12	305	62	485	100	12.5	Excellent	1
		EAS 14	356	62	536	100	12.5	Excellent	1
		EAS 16	406	62	587	100	12.5	Excellent	1
		EAS 18	457	62	638	100	12.5	Excellent	1
		EAS 20	508	62	700	100	12.5	Excellent	1
		EAC 02	51	50	206	100	12.5	Excellent	3
		EAC 03	76	50	231	100	12.5	Excellent	2
		EAC 04	102	50	257	100	12.5	Excellent	1
		EAC 06	152	50	308	100	12.5	Excellent	1
		EAC 08	203	50	359	100	12.5	Excellent	1
	Corner (C)	EAC 10	254	62	435	100	12.5	Excellent	1
		EAC 12	305	62	485	100	12.5	Excellent	1
		EAC 14	356	62	536	100	12.5	Excellent	1
		EAC 16	406	62	587	100	12.5	Excellent	1
		EAC 18	457	62	638	100	12.5	Excellent	1
rier		EAC 20	508	62	700	100	12.5	Excellent	1

Details

Details	Corner (C)	EAC 08	203	50	359	100	12.5	Excellent	1
Llagge Unternal Flagr		EAC 10	254	62	435	100	12.5	Excellent	1
Usage : Internal Floor		EAC 12	305	62	485	100	12.5	Excellent	1
Joint width : 2"-20"		EAC 14	356	62	536	100	12.5	Excellent	1
		EAC 16	406	62	587	100	12.5	Excellent	1
		EAC 18	457	62	638	100	12.5	Excellent	1
Optional : Vapor/Fire Barrier		EAC 20	508	62	700	100	12.5	Excellent	1

As Prospec Specialties' policy is one of continual progress for the improvement of the company's services to its customers, the company reserves the right to modify the specifications of its products without notice.