

## Features

- System designed for water tight installation
- Resists heavy duty loads
- Ideal for bridges as well as commercial kitchens
- EPDM / Neoprene Seal can be replaced easily and without much tools
- Resistant to -40°C to +150°C ambient temperature
- Available in 304 or 316 grade, Stainless Steel
- Resistant to salt and waste water
- System designed for heavy duty application
- Firmly anchored EPDM / Neoprene Seal is ideal for movement tractability as well as water tightness
- System suitable for minor seismic movements
- No bump structure is ADA compliant

### Straight Application AKS

AK Series

EXT. Application



INT. Application

Heavy Duty



Water

Thermal Movement

FLOOR USE



### Corner Application AKC



## Details

Usage : Floor

Joint width : 1" - 4"

Optional : Fire Barrier

Application	Code	JO	SH	SW	± Movement (%)			Load (Ton)
					Horizontal	Vertical	Shear	
Straight (S)	AKS 01	25	33	122	50	50	*	5
	AKS 02	51	33	143	50	50	*	5
	AKS 03	76	33	170	50	50	*	5
	AKS 04	102	33	194	50	50	*	5
Corner (C)	AKC 01	25	33	74	50	50	*	5
	AKC 02	51	33	96	50	50	*	5
	AKC 03	76	33	123	50	50	*	5
	AKC 04	102	33	148	50	50	*	5

As Prospec Specialties' policy is one of continual progress for the improvement of the company's services to its customers, the company reserves the right to modify the specifications of its products without notice.