


Features

- System designed surface mount installation
- Central plate allows swift shift between positive and negative movements
- For excellent result, choose to powder coat the cover plate to match neighboring wall finish
- System allows full seismic movements
- System allows excellent shear movements
- Factory formed transitions available
- Vapor Barrier is standard with this system

Straight Application DBS




Powder Coat Finish:
Any RALColor



Anodized
Finishes:



Corner Application DBC



DB
Series

EXT.
Application

Seismic
Movement

WALL
USE

ROOF
USE

Details

Usage : Wall/Roof

Joint width : 2"-12"

Optional : Fire Barrier

Application	Code	JO	SH	SW	± Movement (%)			Load (Ton)
					Horizontal	Vertical	Shear	
Straight (S)	DBS 02	51	33	150	50	50	Excellent	*
	DBS 03	76	33	175	50	50	Excellent	*
	DBS 04	102	33	200	50	50	Excellent	*
	DBS 06	152	33	250	50	50	Excellent	*
	DBS 08	203	33	300	50	50	Excellent	*
	DBS 12	305	33	400	50	50	Excellent	*
Corner (C)	DBC 02	51	33	87	50	50	Excellent	*
	DBC 03	76	33	115	50	50	Excellent	*
	DBC 04	102	33	141	50	50	Excellent	*
	DBC 06	152	33	216	50	50	Excellent	*
	DBC 08	203	33	268	50	50	Excellent	*
	DBC 12	305	33	420	50	50	Excellent	*

As Prospec Specialties' policy is one of continual progress for the improvement of the company's services to its customers, the company reserves the right to modify the specifications of its products without notice.