

Product and Company Identification

Product Name: GH Series  
 Manufacturer's Name: Prospec Specialties Inc.  
 Suite 400, 3601, Highway 7,  
 Markham ON, L3R 0M3, Canada  
 Emergency #: (888) 749-8456  
 Date Prepared: June, 2013


Table 1: System Details

Application	Code	JO	SH	SW	WH	± Movement (%)			Load
		Millimeter				Hor.	Ver.	Shear	
Straight (S)	GHS 08	203	129	310	*	25	25	Excellent	Vehicular
	GHS 10	254	129	385	*	25	25	Excellent	Vehicular
	GHS 12	305	129	460	*	25	25	Excellent	Vehicular
	GHS 16	406	129	610	*	25	25	Excellent	Vehicular
	GHS 20	508	129	760	*	25	25	Excellent	Vehicular
Corner (C)	GHC 08	203	129	310	120	25	25	Excellent	Vehicular
	GHC 10	254	129	385	120	25	25	Excellent	Vehicular
	GHC 12	305	129	460	120	25	25	Excellent	Vehicular
	GHC 16	406	129	610	120	25	25	Excellent	Vehicular
	GHC 20	508	129	760	120	25	25	Excellent	Vehicular

JO = Joint Opening    SH = System Height    SW = Sight Width    WH = Wall Height

Key to System Features (Straight Application)

1. Continuous sand-blasted center Plate of aluminum, grade 6061-T6
2. Self-tapping stainless steel screw
3. Closed cell, cross linked, heavy duty
4. Micro sealant tape
5. Concesive epoxy adhesive
6. Continuous stiffing rod of aluminum, Grade 6061-T6
7. Concrete slab



Key to System Features (Corner Application)

1. Continuous sand-blasted corner plate of Aluminum, grade 6061-T6
2. Flat head, countersunk screw (by others)
3. Closed cell, cross linked, heavy duty Water tight foam cell
4. **Micro sealant tape**
5. **Concrete epoxy adhesive**
6. Concrete wall (by others)
7. Concrete slab (by others)

